



FOAMCLEAN™

MOBILE AND WALL MOUNT FOAM CLEANING SYSTEMS

FoamClean is designed to reliably produce consistent and controllable foam quality through the use of premixed foam cleaning chemicals. The FoamClean Mobile and Wall Mount Foamer dispenses a rich lather of foam at 190 lit/min (foam) [50 gal/min (foam)] with a projection distance of up to 9 meters (30 feet).

“Efficient, Reliable, and Convenient”



**FoamClean Mobile Foamer
57 liter (15 gallon)**



**FoamClean Mobile and
Wall Mount Foamer
is powered by the
15 LPM or 18.9 LPM
(4 GPM or 5GPM)
air operated pump**


- Super durable, Polyethylene hand-truck is chemical and corrosion resistant
- High foaming capacity
- Most versatile foam quality of any air operated system
- Long lasting, Polypropylene air operated pump with Viton, Santoprene or Teflon seals
- Longer throw and broader coverage
- Air pump is engineered for aggressive acids, alkalines, and chlorine
- Simple operation and user friendly

INDUSTRIAL SYSTEMS

KNIGHT

IDEX
FLUID & METERING

Air Operated Pump




Knight's FoamClean Mobile and Wall Mount system is powered by 18.9 LPM (5 GPM) Polypropylene double-diaphragm pump with Viton or Santoprene seals or 15 LPM (4 GPM) pump with Teflon seals for extended product life, giving you maintenance-free pump operation. The pump is protected in a chemical and corrosion resistant Polyethylene case protecting the pump for years of reliable service.

Aqua-Minder

57 L (15 gal) Dilution Management Unit

The Aqua-Minder automatically mixes cleaning chemical with water and maintains chemical supply level at all times. The Aqua-Minder saves time, increases workplace safety and improves efficiency in all cleaning processes. Can be used on Car Wash, with FoamClean Foamers, filling scrubbers and many other Industrial applications.



FOAMCLEAN SPECIFICATIONS

	Wall Mount FCW-5.0S, Mobile FCM-5.0S,	Wall Mount FCW-5.0V, Mobile FCM-5.0V	Wall Mount FCW-4.0T, Mobile FCM-4.0T
Chemical Compatibility	Acids, Chlorinated Cleaners, Alkalines, Soaps	Acids, Chlorinated Cleaners, D-limonene, Hydrocarbons	All Acids, Chlorinated Cleaners, Caustics, Alkalines
Air Pump Materials	Santoprene	Viton	Teflon
Foam Output	190 Liters/Minute 50 Gallons/Minute	190 Liters/Minute 50 Gallons/Minute	190 Liters/Minute 50 Gallons/Minute
Foaming Distance	9 Meters 30 Feet	9 Meters 30 Feet	9 Meters 30 Feet
Air Consumption	1.4 to 6.9 bar, 20-100 PSI	1.4 to 6.9 bar, 20-100 PSI	5-10 bar, 40-80 PSI
Hose	15 m (50 ft) Reinforced, 3/4" ID w/Wand	15 m (50 ft) Reinforced, 3/4" ID w/Wand	15 m (50 ft) Reinforced, 3/4" ID w/Wand

Applications and Benefits



FoamClean foamers have a higher and longer throw than competitors with a projection distance of 30 feet (9 meters).



The dryness or wetness of the foam can be adjusted for different cleaning applications with a simple turn of a knob.



FoamClean produces consistent foam quality to adhere to irregular surfaces and provide better coverage than liquid cleaning chemicals.



FoamClean can be used throughout the food processing, transportation, dairy, industrial, and agricultural industries.

ORDERING INFORMATION

FOAMCLEAN WALL MOUNT FOAMER SYSTEM

PART #	DESCRIPTION
7649352	Wall Mount, 18.9 ltr/min (5 GPM) Air Operated Pump w/Santoprene Seals/Diaphragm
1800980	57 liters (15 Gallon) Heavy-Duty Polypropylene Tank w/Cap
7113500	Aquaminder 15 LPM (4 GPM) Proportioning System w/ Vacuum Breaker
7113510	Aquaminder 15 LPM (4 GPM) Proportioning System w/o Vacuum Breaker

DIMENSION / WEIGHT (w/HOSE)
W 71cm x H 31cm x D 20cm/13.6 kg. (28" x 12" x 8"/30 lbs.)
H 55.9cm x D 50.7cm/3.8 kg. (22" x 16"/8 lbs.)

FOAMCLEAN MOBILE FOAMER SYSTEM

PART #	DESCRIPTION
7649342	Mobile, 18.9 ltr/min (5 GPM) Air Operated Pump w/Santoprene Seals/Diaphragm
7649343	Mobile, 18.9 ltr/min (5 GPM) Air Operated Pump w/Viton/Diaphragm
7649316-EU	Mobile, 15 ltr/min (4 GPM) Air Operated Pump w/Teflon Seals/Diaphragm

DIMENSION / WEIGHT (w/HOSE)
W 42cm x H 115cm x D 61cm/22.2 kg. (17" x 45" x 24"/49 lbs.)
W 42cm x H 115cm x D 61cm/22.2 kg. (17" x 45" x 24"/49 lbs.)
W 42cm x H 115cm x D 61cm/23.1 kg. (17" x 45" x 24"/51 lbs.)

KNIGHT LIMITED WARRANTY

Knights controls and pump systems are warranted against defects in material and workmanship for a period of ONE YEAR. All Electronic Control Boards have a TWO YEAR warranty. Warranty applies only to the replacement or repair of such parts when returned to the factory with a KRA number, freight prepaid and found to be defective upon factory inspection. Rubber and synthetic rubber parts such as "O" rings, diaphragms, squeeze tubing and gaskets are considered expendable and are not covered under warranty. Warranty does not cover liability resulting from performance of this equipment nor the labor to replace this equipment. Product abuse or misuse voids warranty. Knight products are not for use in potentially explosive environments. Any use of our equipment in such an environment is at the risk of the user. Knight does not accept any liability in such circumstances.

KNIGHT DISCLAIMER

The information and specifications included in this publication were in effect at the time of approval for printing. Knight, LLC, reserves the right, however, to discontinue or change specifications or design at any time without notice and without incurring any obligation whatsoever.



Knight Europe
Tel +44(1323)514.855
Fax +44(1323)514.828

Knight U.S.
Toll Free (800)854-3764
Tel (949) 595-4800
Fax (949)595-4801

Knight Canada
Tel (905)542-2333
Fax (905)542-1536

Knight Australia
Tel +61(02)4223.7450
Fax +61(02)4271.8136

Knight N. Asia
Tel +82(2)3481.6683
Fax +82(2)3482.5742

Knight S. Asia
Tel +65.9170.0984
Fax +65.6489.6723